

EXTERIOR






INTERIOR



Light spacious

and comfortable






Advance driving control system



Advance On-Live security system

DIMENSION





SYSTEM



TECHNICAL SPECIFICATION

| SPECIFICATION | |
|-------------------------|--|
| Seat number | 24 + 2 + 1 + 32 standing |
| Overall dimensions (mm) | 10510 x 2500 x 3350 |
| Wheelbase (mm) | 5100 |
| Gross Weight (kg) | 16000 |
| Max. speed (km/h) | 70 |
| Turning radius (mm) | 10 |
| Curb Weight (kg) | 11800 |
| STANDARD CHASSIS | |
| Motor | DANA TM4 Electric Driving Motor MD130. Max. Power200KW, |
| MOTO | Max. Torque3100Nm |
| Electric control system | Higer pure electric control system |
| Battery | CATL LiFe PO4 power battery 315.1kwh |
| | |
| Suspension Steering | Front 2 rear 4 air suspension Electric Power Steering |
| Axle | Disc in front/disc in rear |
| | WABCO ABS, front and rear disc brake |
| Braking Tire | |
| | 11R22.5 tubeless tire, without tire |
| Driving range | ≥ 270km (testing condition: speed 40km/h) |
| Chassis type | RHD, Low Entrance |
| AC | HIGER Electric air conditioner |
| Painting | Painting Design |
| | Solid paint for whole body |
| Door | Front single and middle double pneumatic inner-swing passenger |
| | door, driver door |
| Seats | Passenger seats with PVC cover |
| Window | Sealed side window, white color |
| Audio Visual | AM/FM, Hard disc player, 1x15" LCD TV |
| Rear-view mirror | Luxury electrical rear-view mirror |
| Floor | Anti-attrition floor leather |
| | Front windows sun visor |
| | Digital Clock |
| | One Wheelchair area (OKU) Manual folding ramp for wheelchair |
| | at middle door |
| | Colorful middle door and rear reverse camera |
| | 3pcs LED destination board (front, left, rear) |
| | Six-camera CCTV system |
| | 10pcs stop buttons for passengers |
| | 8pcs safety hammer |
| | Stainless steel handrails |
| | First aid box |
| | China GB standard plug in charger |
| | · · |







