

# G-BUS

## DIESEL BUS - 10M



### INTERIOR



### TECHNICAL SPECIFICATION

#### PERFORMANCE SPECIFICATION

Manufacturing's Max. Total Mass (kg)	16500
Front/Rear Axle (kg)	5500/11000
Complete Vehicle Curb Mass (kg)	10500
Passenger Capacity (sitting/standing)	32+2+1 / 42 (65)
Max. Speed (km/h)	80
Max. Gradeability (%)	25
Turning Circle diameter (m)	20
Fuel Tank Capacity (L)	200

#### DIMENSION

Overall L x W x H (mm)	10670 x 2480 x 3200
Inner Height (mm)	2250
Wheelbase (mm)	5250
Mini. Ground Clearance (mm)	200
Approach/ Departure Angle (degree)	7deg/7deg

#### ENGINE SPECIFICATION

Engine Model (Yunchai Diesel)	YC6G270-30
Engine Capacity (cc)	7800
Max. Power (HP@rpm)	270@2200
Max. Torque (Nm/rpm)	1080/1600
Fuel Type	Diesel
Fuel Consumption (L/km)	24
Transmission (Automatic)	VOITH A/T D854.3E
Emission Standard	Euro III

#### CHASSIS

Chassis type	RHD, Low-floor, Rear Engine
Clutch	Diaphragm spring clutch
Propeller Shaft	Strengthened propeller shaft
Suspension System	Air suspension
Braking System	Dual-circuit service brake, FR&RR Disc, with ABS
Steering System	Power Steering
Automatic Slack Adjuster	Standard
Automatic fire	Auto fire extinguisher in engine cabin
Tyre & Wheel	275/70 R22.5, with spare

#### BODY

Air Conditioner	HIGER, 30000 cal/h
Bus Reverse Monitor	Standard
Destination Board	3 pcs, LED, front-left-rear
Monitor System	Color Reverse Camera
Digital Clock	Standard
CCTV	Six-camera system
Lighting System	Standard
Sun Visor	Standard
Ventilator	Electric type
Seats	With PVC cover ; high-backrest driver seat
Floor	Advanced wear-resistance quartz sand floor leather
Passenger Door	Front/middle pneumatic inner swing passenger door, middle door with alarm lamp and warning tone
Window	Standard, sealed-side with white cover
Emergency Roof	Standard
Rear-view	Luxury pole style wide-field rear-view mirror
Safety Hammer	100pcs Standard
Fire extinguisher	Standard
Handrail	Stainless steel, Standard



www.goautovan.my



Go Auto Van

**GO AUTO**